

MTLE1814c

MTLE SERIES 15_{MIN} UL-RATED HIGH-SECURITY BURGLARY SAFES



SPECIFICATIONS

EXTERIOR [HWD]	INTERIOR [HWD]	INTERIOR [CU.FT.]	SHELVING [NO.]	WEIGHT
25" x 21" x 21 1/2"	18" x 14" x 12"	1.8	1	710 lbs

SAFE FEATURES

BODY & DOOR

- All steel construction
- Door constructed with a 2-3/4" defense barrier of outer & inner steel plates creating a single structure, enclosing high-density fire & burglary resistant composite material
- Defense barrier houses a proprietary amalgamation of nuggets & steel fibers to withstand concentrated attacks with the most sophisticated equipment used by burglars
- Formed body has a total protective thickness of 3-1/2" enclosing a high-density fire resistant composite material of nuggets & steel fibers

- Entire boltwork mechanism is also protected by a spring operated boltwork detent system
- Heavy-duty solid steel hinges
- 2 hour, 350°F factory fire rating [Tested in temperatures up to 1850°F]
- 6 massive 1-1/2" diameter chrome plated solid steel locking bolts, each bolt moves deep into the body's protected bolt chambers
- 1 High strength adjustable shelves

LOCK

- Lock protected by a drill resistant hard plate & punch-activated reloading system
- Spy-Proof U.L. Listed Group 2 Combination Lock [Offered with TL-30 Series]
- U.L. Listed Group 2 Combination Lock

LOCK OPTIONS



MTLE2518c

MTLE SERIES 15_{MIN} UL-RATED HIGH-SECURITY BURGLARY SAFES



SPECIFICATIONS

EXTERIOR [HWD]	INTERIOR [HWD]	INTERIOR [CU.FT.]	SHELVING [NO.]	WEIGHT
32" x 25" x 25 1/2"	25" x 18" x 16"	4.2	1	1105 lbs

SAFE FEATURES

BODY & DOOR

- All steel construction
- Door constructed with a 2-3/4" defense barrier of outer & inner steel plates creating a single structure, enclosing high-density fire & burglary resistant composite material
- Defense barrier houses a proprietary amalgamation of nuggets & steel fibers to withstand concentrated attacks with the most sophisticated equipment used by burglars
- Formed body has a total protective thickness of 3-1/2" enclosing a high-density fire resistant composite material of nuggets & steel fibers

- Entire boltwork mechanism is also protected by a spring operated boltwork detent system
- Heavy-duty solid steel hinges
- 2 hour, 350°F factory fire rating [Tested in temperatures up to 1850°F]
- 6 massive 1-1/2" diameter chrome plated solid steel locking bolts, each bolt moves deep into the body's protected bolt chambers
- 1 High strength adjustable shelves

LOCK

- Lock protected by a drill resistant hard plate & punch-activated relocking system
- Spy-Proof U.L. Listed Group 2 Combination Lock [Offered with TL-30 Series]
- U.L. Listed Group 2 Combination Lock

LOCK OPTIONS



MTLE3524c

MTLE SERIES 15_{MIN} UL-RATED HIGH-SECURITY BURGLARY SAFES



SPECIFICATIONS

EXTERIOR [HWD]	INTERIOR [HWD]	INTERIOR [CU.FT.]	SHELVING [NO.]	WEIGHT
42" x 31" x 29½"	35" x 24" x 20"	9.7	2	1674 lbs

SAFE FEATURES

BODY & DOOR

- All steel construction
- Door constructed with a 2-¾" defense barrier of outer & inner steel plates creating a single structure, enclosing high-density fire & burglary resistant composite material
- Defense barrier houses a proprietary amalgamation of nuggets & steel fibers to withstand concentrated attacks with the most sophisticated equipment used by burglars
- Formed body has a total protective thickness of 3-½" enclosing a high-density fire resistant composite material of nuggets & steel fibers

- Entire boltwork mechanism is also protected by a spring operated boltwork detent system
- Heavy-duty solid steel hinges
- 2 hour, 350°F factory fire rating [Tested in temperatures up to 1850°F]
- 6 massive 1-½" diameter chrome plated solid steel locking bolts, each bolt moves deep into the body's protected bolt chambers
- 2 High strength adjustable shelves

LOCK

- Lock protected by a drill resistant hard plate & punch-activated relocking system
- Spy-Proof U.L. Listed Group 2 Combination Lock [Offered with TL-30 Series]
- U.L. Listed Group 2 Combination Lock

LOCK OPTIONS



MTLE4524c

MTLE SERIES 15_{MIN} UL-RATED HIGH-SECURITY BURGLARY SAFES



SPECIFICATIONS

EXTERIOR [HWD]	INTERIOR [HWD]	INTERIOR [CU.FT.]	SHELVING [NO.]	WEIGHT
52" x 31" x 29½"	45" x 24" x 20"	12.5	3	2003 lbs

SAFE FEATURES

BODY & DOOR

- All steel construction
- Door constructed with a 2-¾" defense barrier of outer & inner steel plates creating a single structure, enclosing high-density fire & burglary resistant composite material
- Defense barrier houses a proprietary amalgamation of nuggets & steel fibers to withstand concentrated attacks with the most sophisticated equipment used by burglars
- Formed body has a total protective thickness of 3-½" enclosing a high-density fire resistant composite material of nuggets & steel fibers

- Entire boltwork mechanism is also protected by a spring operated boltwork detent system
- Heavy-duty solid steel hinges
- 2 hour, 350°F factory fire rating [Tested in temperatures up to 1850°F]
- 6 massive 1-½" diameter chrome plated solid steel locking bolts, each bolt moves deep into the body's protected bolt chambers
- 3 High strength adjustable shelves

LOCK


- Lock protected by a drill resistant hard plate & punch-activated relocking system
- Spy-Proof U.L. Listed Group 2 Combination Lock [Offered with TL-30 Series]
- U.L. Listed Group 2 Combination Lock

LOCK OPTIONS



MTLE5524c

MTLE SERIES 15_{MIN} UL-RATED HIGH-SECURITY BURGLARY SAFES



SPECIFICATIONS

EXTERIOR [HWD]	INTERIOR [HWD]	INTERIOR [CU.FT.]	SHELVING [NO.]	WEIGHT
62" x 31" x 29½"	55" x 24" x 20"	15.3	3	2343 lbs

SAFE FEATURES

BODY & DOOR

- All steel construction
- Door constructed with a 2-¾" defense barrier of outer & inner steel plates creating a single structure, enclosing high-density fire & burglary resistant composite material
- Defense barrier houses a proprietary amalgamation of nuggets & steel fibers to withstand concentrated attacks with the most sophisticated equipment used by burglars
- Formed body has a total protective thickness of 3-½" enclosing a high-density fire resistant composite material of nuggets & steel fibers

- Entire boltwork mechanism is also protected by a spring operated boltwork detent system
- Heavy-duty solid steel hinges
- 2 hour, 350°F factory fire rating [Tested in temperatures up to 1850°F]
- 10 massive 1-½" diameter chrome plated solid steel locking bolts, each bolt moves deep into the body's protected bolt chambers
- 3 High strength adjustable shelves

LOCK

- Lock protected by a drill resistant hard plate & punch-activated relocking system
- Spy-Proof U.L. Listed Group 2 Combination Lock [Offered with TL-30 Series]
- U.L. Listed Group 2 Combination Lock

LOCK OPTIONS



MTLE6528c

MTLE SERIES 15_{MIN} UL-RATED HIGH-SECURITY BURGLARY SAFES



SPECIFICATIONS

EXTERIOR [HWD]	INTERIOR [HWD]	INTERIOR [CU.FT.]	SHELVING [NO.]	WEIGHT
72" x 35" x 29½"	65" x 28" x 20"	21.1	4	3153 lbs

SAFE FEATURES

BODY & DOOR

- All steel construction
- Door constructed with a 2-¾" defense barrier of outer & inner steel plates creating a single structure, enclosing high-density fire & burglary resistant composite material
- Defense barrier houses a proprietary amalgamation of nuggets & steel fibers to withstand concentrated attacks with the most sophisticated equipment used by burglars
- Formed body has a total protective thickness of 3-½" enclosing a high-density fire resistant composite material of nuggets & steel fibers

- Entire boltwork mechanism is also protected by a spring operated boltwork detent system
- Heavy-duty solid steel hinges
- 2 hour, 350°F factory fire rating [Tested in temperatures up to 1850°F]
- 10 massive 1-½" diameter chrome plated solid steel locking bolts, each bolt moves deep into the body's protected bolt chambers
- 4 High strength adjustable shelves

LOCK

- Lock protected by a drill resistant hard plate & punch-activated relocking system
- Spy-Proof U.L. Listed Group 2 Combination Lock [Offered with TL-30 Series]
- U.L. Listed Group 2 Combination Lock

LOCK OPTIONS



MTLE7236c

MTLE SERIES 15_{MIN} UL-RATED HIGH-SECURITY BURGLARY SAFES



SPECIFICATIONS

EXTERIOR [HWD]	INTERIOR [HWD]	INTERIOR [CU.FT.]	SHELVING [NO.]	WEIGHT
79" x 43" x 32 1/2"	72" x 36" x 23"	34.5	4	3880 lbs

SAFE FEATURES

BODY & DOOR

- All steel construction
- Door constructed with a 2-3/4" defense barrier of outer & inner steel plates creating a single structure, enclosing high-density fire & burglary resistant composite material
- Defense barrier houses a proprietary amalgamation of nuggets & steel fibers to withstand concentrated attacks with the most sophisticated equipment used by burglars
- Formed body has a total protective thickness of 3-1/2" enclosing a high-density fire resistant composite material of nuggets & steel fibers

- Entire boltwork mechanism is also protected by a spring operated boltwork detent system
- Heavy-duty solid steel hinges
- 2 hour, 350°F factory fire rating [Tested in temperatures up to 1850°F]
- 10 massive 1-1/2" diameter chrome plated solid steel locking bolts, each bolt moves deep into the body's protected bolt chambers
- 4 High strength adjustable shelves

LOCK

- Lock protected by a drill resistant hard plate & punch-activated reloading system
- Spy-Proof U.L. Listed Group 2 Combination Lock [Offered with TL-30 Series]
- U.L. Listed Group 2 Combination Lock

LOCK OPTIONS

